Finding Your Connection Details

Finding your credentials

Go to portal → **Connect**. This page shows connection details for every deployed service, including endpoints, usernames, and passwords.

- Passwords are masked by default — click to reveal.
- Copy buttons next to each field for quick clipboard access.
- Only deployed (enabled) services appear.

Service endpoints

Public URLs

Services with a web interface are reachable at `https://<your-slug>-<service>.compacthive.dev`:

Service	URL pattern
Woodpecker CI	`<your-slug>-ci.compacthive.dev`
Grafana (part of Monitoring)	`<your-slug>-grafana.compacthive.dev`
Forgejo	`<your-slug>-forgejo.compacthive.dev`
MinIO Console	`<your-slug>-minio.compacthive.dev`
Uptime Kuma	`<your-slug>-status.compacthive.dev`
FileBrowser	`<your-slug>-files.compacthive.dev`
Custom apps	`<your-slug>-<app-name>.compacthive.dev`

Internal-only services

These don't have a public URL — they're only reachable from within your namespace, or via the Headscale VPN add-on (Business tier and up):

Service	Internal address	Port
PostgreSQL	`pg-<tenant-id>-rw.<namespace>.svc`	5432
KeyDB cache	`cache-<tenant-id>.<namespace>.svc`	6379
MinIO (S3 API)	`minio-<tenant-id>.<namespace>.svc`	9000

Credential lifecycle

- Credentials are generated once during initial deployment and stored as Kubernetes Secrets.
- They survive service restarts and redeployments.
- They are deleted only when the tenant namespace (or the specific service) is removed.
- There's no self-service rotation UI today — if you need to rotate a service credential, disable and re-enable the service.

Revision #1
Created 2026-11-03 14:21:30 UTC by Docs Sync
Updated 2026-11-03 14:21:30 UTC by Docs Sync